

American Foam Technologies, Inc.

HC 37 Box 317 H

Lewisburg, WV 24901

Phone #: (304) 497-3000 Fax #: (304) 497-3001

Material Safety Data Sheet

PRODUCT IDENTIFICATION

Trade Name: All Grades AFT Rigid Foam
Chemical Name: Rigid Polyurethane Foam
Synonyms: Urethane Foam

Chemical Family: Urethane Polymer
Formula: N/A
Date Prepared: 11/03/98

INGREDIENTS- HAZARD CLASSIFICATION

Name:	%	TLV/PEL
None.		

PHYSICAL DATA

Boiling Point (°F): N/A
Solubility in Water: Insoluble
Appearance and Odor:

Specific Gravity: 0.005 - 0.35
% Volatile by Volume: 0
Fine-celled rigid foam, normally tan but can be any color, possible amine odor if freshly cut, hardness varies with density.

FIRE AND EXPLOSION HAZARD DATA

Flash Point (test method): Not applicable. The ignition temperature of rigid polyurethane foam is in the range of 700 - 800 °F. The temperature must exceed 300 °F for a period of time before the occurrence of degradation, which may lead eventually to self-ignition. At this temperature most solid combustible material will exhibit signs of charring, one of the first steps in ignition.

Extinguishing Media: Water, dry chemicals, CO₂. Use water for larger fires.

Special Fire Fighting Procedures: A self-contained breathing apparatus should be worn to protect against toxic and irritating vapors.

Unusual Fire and Explosion Hazards: When foam burns it produces a large volume of dense smoke that presents a major hazard in that it can cause panic and disorientation and inhibit ability to escape.

REACTIVITY DATA

Stability: Stable
Polymerization: Will not occur
Incompatibility: None.

Conditions to Avoid: N/A
Conditions To Avoid: N/A

Hazardous Decomposition Products: When burned; CO, CO₂, NO_x, aliphatic fragments, traces of HCN, benzene, toluene; possibly HF, HCl, HBr, oxides of phosphorus.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of American Foam Technologies, Inc.. The data on this sheet relates only to the specific material designated herein. North Carolina Foam Industries assumes no legal responsibility for use or reliance upon these data.

HEALTH HAZARD DATA

Permissible Exposure Limit: Not Applicable

Effects of Overexposure: Not Applicable

First Aid Procedures: Not Applicable

SPECIAL PROTECTION INFORMATION

Respiratory Protection: Use dust mask when fabrication dust is in the air.

Ventilation: Not Applicable.

Eye Protection: Goggles when foam dust is in the air.

Gloves: Not Applicable

Other: Not Applicable

SPILL OR LEAK PROCEDURES

Not Applicable

SPECIAL PRECAUTIONS

Where any foam is sprayed in building interiors its exposed surface should be protected from fire hazard by 1/2" Portland cement plaster or 1/2" gypsum board or equivalent. For the prediction of fire hazard in construction, refer to SPI "Fire Safety Guidelines for Use of Rigid Polyurethane Foam Insulation in Building Construction" (U-100R). For proper use refer to any of the following codes:

Southern Standard Building Code, Section 2603

BOCA Basic Building Code, Section 2603

ICBO Uniform Building Code, Section 2602

Rigid foam dust from fabricating operations is an irritant and is flammable. Dust should be collected at the point of generation and stray dust should be regularly swept up.

Large amounts of rigid polyurethane foam assembled in one place, such as for processing into finished products or in storage, present a potential fire hazard. Once ignited, these foams may spread flame rapidly and produce intense heat, dense smoke and toxic gases. Raw foam and fabricated items should be stored indoors, away from fabricating operations, and be protected by automatic sprinklers. Access aisles should be maintained between foam piles.

Ignition sources such as smoking materials, naked lights, open flames and exposed heating elements should be kept away from storage and fabricating areas. Scrap foam should not be permitted to accumulate but should be disposed of promptly.

In case of fire, drench the burning foam with water from a fire hose with a spray nozzle.

Fire fighters should use self-contained breathing apparatus.

General fire safety recommendations such as management interest, personnel training, construction, location, alarms, identification of fire causes, house-keeping, smoke-venting, floor drainage, etc., that apply to storage of other combustible materials also apply to the storage of rigid polyurethane foam.